



3468S $33\frac{7}{16}$ " x $67\frac{3}{16}$ " x 24"

FOR MAINTENANCE OR REPAIR: The shell can be removed by flipping the tub over, locating and removing the 4 plastic nubs and loosening the securing screws underneath. Then the entire shell can easily be removed.

GENERAL SPECIFICATIONS:

Material Acrylic

Plumbed Weight: 125lbs / 57kg Soaker Weight: 95lbs / 43kg Average Fill: 50 gal to above jet level ELECTRICAL SPECIFICATIONS:

Required Electrical Service 110 Volt
Air Bath or Whirlpool 1-15 amp GFCI
Whirlpool with Inline Heater
Whirlpool and Air Service 110 Volt
1-20 amp GFCI
1-20 amp GFCI

Soaker

PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
Soaker	Soaking bath - no jets, textured bottom	3468SS
Whirlpool	8 Adjustable pointed-massage jets, 1-hp pump, textured bottom	3468SH
Air Bath	22 Air jets, Air blower, Textured bottom	3468SA
Whirlpool and Air	Adjustable pointed-massage jets, 1-hp pump, Air jets, Air blower, textured bottom	3468SD

- OPTIONS
- · Colors Available White
- Quick Ship reduces lead time call for availability
- Inline Heater with Pump Whirlpool or Whirlpool and Air Bath
- Lift & Turn Drain Kit -Chrome, Brushed Nickel, White
- Color Match Jets.

IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Please measure tub on-site before installation
- •Jet, pump & blower locations are predetermined and cannot be changed.
- •Make certain the floor structure is level and adequate to support installation.
- •Building codes require that a panel(s) be constructed to allow ample clearance for plumbing repairs and pump service or removal
- •Please note that installer(s) must be certify or warranty will be voided.
- Specifications and configurations are subject to change without notice.
- Measurements are +1/2" and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.